

JPL WEATHERTOUCH

JPL WEATHERTOUCH

Weather touch is a premium exterior emulsion specially developed for areas exposed to high moisture and humidity. Its anti-fungal formulation prevents wall damage, while the smooth finish and superior washability ensure long-lasting beauty and easy maintenance. Water-based, weather resistant, and smooth finishing.



TECHNICAL ADVANTAGES

- Anti-fungal formulation prevents wall damage in damp conditions
- Superior washability — easy maintenance for lasting beauty
- Weather resistant — with stands rain and humidity
- Smooth finish gives walls a premium elegant look
- Water-based eco-friendly formulation

PACKAGE AVAILABLE

Shelf Life - 12 Months

Color - White



30 Ltr. Bucket

WHY SPECIFY

- Apply the first coat of Terrashield & allow it to dry for at least 6 to 8 hours.
- Apply 45 GSM Nylon Mesh while the first coat is wet
- Apply the second coat of Terrashield with a roller or a trowel.
- Remove the excess material with emery paper (no. 320) by light sanding vertically and horizontally to get a smooth, seamless surface.
- The surface is ready to be painted within 96 hours after completion of the second coat.

APPLICATIONS

- Exterior walls in high-humidity and moisture - prone areas
- Terraces and external soffits
- Surfaces requiring anti-fungal protection
- Premium exterior facade finishing

TECHNICAL ADVANTAGES

- Anti-fungal formulation prevents wall damage in damp conditions
- Superior washability — easy maintenance for lasting beauty
- Weather resistant — with stands rain and humidity
- Smooth finish gives walls a premium elegant look
- Water-based eco-friendly formulation

NABL TEST RESULTS

Carried out as per ASTM Standards by SriRam and Eurofin Labs

Class 1 or A	Fire Retardant Surface rating
3.2 MPA	Compressive Strength
5.8 MPA	Tensile Strength
1.9 MPA	Flexural Strength
24.3% Absorption	after submerged for 24hrs.
1.0 MPA	Pull of Strength
2.04 (mm) No cracking	Crack Bridging Test

COVERAGE

DESCRIPTION	VALUE
Base material	Water Based
Viscosity at 30°C	45 Sec
Weight / litre	1.26 KG/LTR
IS standard	IS-15489
pH	8
Sheen	Mild Sheen
Surface drying	30 - 60 Minutes